

(11)Publication number:

11-017227

(43) Date of publication of application: 22.01.1999

(51)Int.CI.

H01L 33/00

(21)Application number : 09-171691

(71)Applicant: IWASAKI ELECTRIC CO LTD

(22)Date of filing:

27.06.1997

(72)Inventor: SUEHIRO YOSHINOBU


HATANAKA MITSUSACHI


(54) REFLECTING TYPE LIGHT -EMITTING DIODE AND ARRAY BODY OF LIGHT -EMITTING DIODE

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a reflecting type light-emitting diode and an array body of light-emitting diode capable of improving heat radiation, by stably holding the positional accuracy of a light-emitting element against a recessed surface type reflecting surface.

SOLUTION: A light emitting element 11 is mounted almost at the center of the first lead portion 12a, and the light-emitting element 11 and a second lead portion 12b are connected by a wire 13. The light-emitting element 11, a first lead portion 12a, a second lead portion 12b and a part of a third lead portion 12c are sealed by a light transmitting lateral 14. The third lead portion 12c is attached to a supporting portion 17. The first lead portion 12a is formed in such a manner that a recessed reflecting surface 15 is crossed almost linearly when the recessed reflecting surface 15 is seen from the front. An end portion a of the first lead portion and the second lead portion 12b, and an end portion β of the first lead portion 12a and the third lead portion 12c are taken out in a reverse direction each other from the side surface of the light transmitting material 14.





LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japanese Patent Office